





D1、D2、D3 with special Jaw-3, refer to P51
D1、D2、D3 皆配合 P51 大開口虎口板



以下為選配產品 ACV-110M



特點

1. 可側立、臥式、直立各種方式加工，且可搭配多台並列式、串聯或並聯加工使用。
2. 新型純氣動增壓，可調整夾持力 0-2000kgf，當空壓源突然消失時，夾持不鬆脫，安全性高，無漏油之虞。
3. 全新角固及防止變形夾持結構，加工時，兼具精度及安全。
4. 依工件大小，調整預留夾持行程 0-4mm。1 秒內即可夾持，操作簡單快速。
5. FCD-60kgs/mm² 球狀石墨鑄鐵 (60kgs) 強力機構設計，抗張力、抗壓強度及機械性質佳。
6. 滑道經熱處理 HRC-55-60 度，保持精度及耐磨性，經久耐用。
7. 本台短小精悍，不佔機台空間，銅件、塑膠、薄件、亦可調整夾持力夾持。

Features

1. The vise can be used vertically, horizontally or stand on one side. Several parallel type vises in series or parallel can be used together.
2. When the pneumatic source disappears suddenly, the clamping force remains unchanged. The safety degree is high. Don't worry about oil leaks.
3. Powerful structure designed with FCD-60 kgs/mm² spherical graphite casting iron has good mechanical performance, and is very resistant to pressure and tension.
4. The slide is heat treated to HRC-55° so as to keep precision and long-wearing. It is very durable.
5. This vise is very compact and rigid, and does not occupy machine space. The clamping force can be adjusted so as to clamp copper, plastic and thin workpieces. precision and enhances rigidity for long service life.
3. Sliding surfaces are hardened to HRC 45°, flexible designed vise jaw is made by high quality steel and hardened HRC 50°.

ITEM NO. 型號	ACV-110
A	472
B	330
C	158
D	120
D1	185
D2	245
D3	325
E	120
F	60
G	19
H	130
I	58
J	188
K	22
L	15
M	18
N	55
O	17
P	191
Clamping Force 夾持力	2000 kgf
Weight 重量	47 kg